

MW302R Router

inalámbrico N multimodo a 300Mbps Mercusysaa

- Wireless
 - Wireless Standards
 - IEEE 802.11b/g/n
 - Frequency
 - 2.4-2.4835GHz
 - Signal Rate
 - 11n: Up to 300Mbps (Dynamic)
 - 11g: Up to 54Mbps (Dynamic)
 - 11b: Up to 11Mbps (Dynamic)
 - Reception Sensitivity
 - 270M: -73dBm@10% PER
 - 130M: -75dBm@10% PER
 - 54M: -77dBm@10% PER
 - 11M: -90dBm@10% PER
 - 6 M: -94dBm@10% PER
 - 1 M: -96dBm@10% PER
 - Transmission Power
 - <20dBm (EIRP)
 - Wireless Security
 - WPA-PSK / WPA2-PSK
 - Wireless Functions
 - Enable/Disable Wireless Radio, WDS
 - Bridging
 - Software
 - WAN Type
 - Dynamic IP/Static IP/PPPoE/PPTP/L2TP
 - Management
 - Access Control, Local Management, Remote Management
 - DHCP
 - Server
 - Port Forwarding
 - Virtual Server, UPnP, DMZ
 - Firewall Security
 - IP and MAC Address Binding
 - Protocols

